

Legend

- Wind Farm Site
- Amended OFTW Corridor
- ✕ Pile Position

Harbour (Common) Seal Density

Proportion per 4 x 4 km Grid Square

- > 0.0 - 0.1 %
- 0.1 - 0.2 %
- 0.2 - 0.3 %
- 0.3 - 0.4 %
- 0.4 - 0.5 %

Area of Behavioural Effect

- 75 dB_(ht)
- 90 dB_(ht)


Area of Permanent Threshold Shift

- 198 dB re. 1 $\mu\text{Pa}^2/\text{s}$ - Fleeing

Harbour Seal Numbers

- | | | |
|--|---|---|
| 1 - 5 | 101 - 200 | 501 - 1,000 |
| 6 - 10 | 201 - 300 | |
| 11 - 20 | | |
| 21 - 30 | | |
| 31 - 50 | | |
| 51 - 100 | 301 - 500 | |

Source: Thompson & Brookes 2011
 SSE Renewables (UK) Ltd. 2013. The concepts and information contained in this document are the copyright of SSE Renewables (UK) Ltd. Use or copying of the document in whole or in part without the written permission of SSE Renewables (UK) Ltd constitutes an infringement of copyright. SSE Renewables (UK) Ltd. does not warrant that this document is definitive nor free of error and does not accept liability for any loss caused or arising from reliance upon information provided herein.



UK Offshore Development
 Figure 6.14i
 Noise Contours Overlaid on Harbour Seal Densities for BOWL A

Drawn: MM	Checked: RJ	Approved: TJM
Date: 03/05/2013	Scale: 1:600,000 @ A3	
Drawing Number: BEA-MAP-EWF-BOWL-350	Revision: 03	
Datum: WGS84	Projection: UTM30N	

