



Legend

- Wind Farm Site
- Amended OFTW Corridor
- x Pile Position
- Noise Contours (dB_(ht) Level)

Maximum dB_(ht) per 4 x 4 km Grid Square

- 50 dB_(ht)
- 55 dB_(ht)
- 60 dB_(ht)
- 65 dB_(ht)
- 70 dB_(ht)
- 75 dB_(ht)
- 80 dB_(ht)
- 85 dB_(ht)
- 90 dB_(ht)
- 100 dB_(ht)
- 110 dB_(ht)
- 120 dB_(ht)
- 130 dB_(ht)

Source: Searoc
 SSE Renewables (UK) Ltd. 2013. The concepts and information contained in this document are the copyright of SSE Renewables (UK) Ltd. Use or copying of the document in whole or in part without the written permission of SSE Renewables (UK) Ltd constitutes an infringement of copyright. SSE Renewables (UK) Ltd. does not warrant that this document is definitive nor free of error and does not accept liability for any loss caused or arising from reliance upon information provided herein.

0 10 20 40 km 0 3 6 12 Nm

UK Offshore Development

Figure 6.7
 Area of Behavioural Effect (dB_(ht))
 for Harbour Seal for BOWLA

Drawn: MM	Checked: TJM	Approved: TJM
Date: 15/02/2013	Scale: 1:1,000,000 @ A3	
Drawing Number: BEA-MAP-EWF-BOWL-341	Revision: 02	
Datum: WGS84	Projection: UTM30N	

