


Legend

- Wind Farm Site
- Amended OFTW Corridor
- x Pile Position
- Noise Contours (dB re. 1 $\mu\text{Pa}^2/\text{s}$)

Maximum dB per 4 x 4 km Grid Square

- 186 dB re. 1 $\mu\text{Pa}^2/\text{s}$ - Fleeing
- 188 dB re. 1 $\mu\text{Pa}^2/\text{s}$ - Fleeing
- 190 dB re. 1 $\mu\text{Pa}^2/\text{s}$ - Fleeing
- 192 dB re. 1 $\mu\text{Pa}^2/\text{s}$ - Fleeing
- 194 dB re. 1 $\mu\text{Pa}^2/\text{s}$ - Fleeing
- 196 dB re. 1 $\mu\text{Pa}^2/\text{s}$ - Fleeing
- 198 dB re. 1 $\mu\text{Pa}^2/\text{s}$ - Fleeing
- 200 dB re. 1 $\mu\text{Pa}^2/\text{s}$ - Fleeing

Source: Searoc
 SSE Renewables (UK) Ltd. 2013. The concepts and information contained in this document are the copyright of SSE Renewables (UK) Ltd. Use or copying of the document in whole or in part without the written permission of SSE Renewables (UK) Ltd constitutes an infringement of copyright. SSE Renewables (UK) Ltd. does not warrant that this document is definitive nor free of error and does not accept liability for any loss caused or arising from reliance upon information provided herein.



UK Offshore Development

Figure 4.8
 Noise Contours for PTS Fleeing for Pinnipeds
 Generated Using the Dose-Response Curve

Drawn: MM	Checked: TJM	Approved: TJM
Date: 19/02/2013	Scale: 1:250,000 @ A3	
Drawing Number: BEA-MAP-EWF-BOWL-373	Revision: 01	
Datum: WGS84	Projection: UTM30N	

