



**Legend**

- Wind Farm Site
- Amended OFTW Corridor
- X Pile Position
- Noise Contours (dB<sub>(HT)</sub> Level)

**Maximum dB<sub>(HT)</sub> per 4 x 4 km Grid Square**

- 50 dB<sub>(HT)</sub>
- 55 dB<sub>(HT)</sub>
- 60 dB<sub>(HT)</sub>
- 65 dB<sub>(HT)</sub>
- 70 dB<sub>(HT)</sub>
- 75 dB<sub>(HT)</sub>
- 80 dB<sub>(HT)</sub>
- 85 dB<sub>(HT)</sub>
- 90 dB<sub>(HT)</sub>
- 100 dB<sub>(HT)</sub>
- 110 dB<sub>(HT)</sub>
- 120 dB<sub>(HT)</sub>
- 130 dB<sub>(HT)</sub>

Source: Searoc  
 SSE Renewables (UK) Ltd. 2013. The concepts and information contained in this document are the copyright of SSE Renewables (UK) Ltd. Use or copying of the document in whole or in part without the written permission of SSE Renewables (UK) Ltd constitutes an infringement of copyright. SSE Renewables (UK) Ltd. does not warrant that this document is definitive nor free of error and does not accept liability for any loss caused or arising from reliance upon information provided herein.

0 10 20 40 km 0 3 6 12 Nm

UK Offshore Development

Figure 4.9  
 Noise Contours for Behavioural Displacement of Pinnipeds Using the Dose-Response Curve

Drawn: MM	Checked: TJM	Approved: TJM
Date: 19/02/2013	Scale: 1:1,000,000 @ A3	
Drawing Number: BEA-MAP-EWF-BOWL-374	Revision: 01	
Datum: WGS84	Projection: UTM30N	

