

Lege	end				
	Beatrice Offshore	Wind Farm	Site		
_	Beatrice Offshore				
	Works Corridor				
	Special Areas of O Designated for Ma				
Harbour Seal Numbers					
Proportion per 4x4m Grid Square					
-	> 0.0 - 0.1 %				
	0.1 - 0.2%				
	0.2 - 0.3 %				
	0.3 - 0.4 %				
	0.4 - 0.5 %				
Behav	vioural Impact Are	as			
75 dBl					
	Backhoe Dredging	n (1m)			
H	Cable Laying (9m				
H					
H	Vessel Noise (29m)				
H	Cable Protection (170m) Trenching (350m)				
Data Source: Subacoustech 2011 and Thompson & Brookes 2011 © British Crown and SeaZone Solutions Limited. All rights reserved. Products licence No. 012010.004. Bathymetry reproduced from the GEBCO Digital Atlas published by the British Oceanographic Data Centre on behalf of IOC and IHO, 2003. SSE Renewables (UK) Ltd. 2012. The concepts and information contained in this document are the copyright of SSE Renewables (UK) Ltd. Use or copying of the document in whole or in part without the written permission of SSE Renewables (UK) Ltd. Constitutes an infringement of copyright. SSE Renewables (UK) Ltd. does not warrant that this document is definitive nor free of error and does not accept liability for any loss caused or arising from reliance upon information provided herein.					
	2.5 5 	10 km	0 1.25	2.5	5 nm
			evelopment		
Figure 24.2					
Predicted Zones of Impact from Noise Associated with the Transmission Works					
fro			h the Trans Harbour P		VVUIKS
Drawn:				Approved:	VR
	1/02/2012				
Date: 01/02/2012 Scale: 1:300,000 @ A3   Drawing Number: BEA-MAP-OFTW-BOWL-199 Revision: 01					
-	WGS84	Projection:		Ľ Š	
Beatrice Offshore Windfarm Ltd					