

OUR VISION

**To create a
world powered
by renewable
energy**



Marine Mammal Collision Risk Modelling

Sound of Islay

18 November 2021

Flex Marine Power

Document history

Author	Gillian Vallejo, Senior Ecological Modeller Suzanne McCarthy, Environmental Consultant	18/11/2021
Checked	Chris Pendlebury, Director of Planning & Environment	18/11/2021
Approved	Chris Pendlebury, Director of Planning & Environment	18/11/2021

Client Details

Contact	Mark Spybey
Client Name	Flex Marine Power
Address	91, Clober Road, Milngavie, Glasgow, G62 7LS

Issue	Date	Revision Details
A	18/11/2021	To issue

Local Office:

Ochil House
Springkerse Business Park
Stirling
FK7 7XE
SCOTLAND
UK
Tel: +44 (0) 1786 542

Registered Office:

The Natural Power Consultants Limited
The Green House
Forrest Estate, Dalry
Castle Douglas, Kirkcudbrightshire
DG7 3XS

Reg No: SC177881

VAT No: GB 243 6926 48

Contents

1. Introduction	1
2. Methods	1
3. Results	3
4. Discussion	4
5. References	4

1. Introduction

Flex Marine Power Ltd, in association with Islay Energy Trust, is proposing to develop a tidal energy generating project in the Sound of Islay. During consultation with NatureScot, it was advised that, as part of the marine licensing application, collision risk modelling should be carried out in order to assess the implications of potential collisions with the tidal device for:

- Harbour seal (*Phoca vitulina*), relating to the South-East Islay Skerries SAC [UK0030067];
- Harbour porpoise (*Phocoena phocoena*), relating to the Inner Hebrides and Minches SAC [UK0030393]; and,
- Grey seal (*Halichoerus grypus*) relating to the Treshnish Isles SAC [UK0030289].

Two rotor sizes are under consideration to be deployed at the site. The device is expected to operate initially with a 3.28 m diameter rotor and subsequently with a 5 m diameter rotor. Both options are considered here.

2. Methods

The Encounter Rate Model (ERM) (SNH, 2016) was used to predict the number of collisions with the tidal device expected per year for harbour seal, harbour porpoise and grey seal. The ERM model is a simplified equation-based model which calculates collision rates as a function of the density of animals present at the site, the area swept by the rotor(s), and the speed of the blades, providing a standardised “order-of-magnitude” estimate of the collisions likely to occur in the absence of any factors drawing animals towards, or away from the devices (e.g. behavioural avoidance of the rotors, effects of hydrodynamic forces or attraction to the high energy flow of water through the turbines or to concentrations of fish sheltering around turbine supports). The model was run using the underwater CRM tool available on the NatureScot website (<https://www.nature.scot/doc/assessing-collision-risk-between-underwater-turbines-and-marine-wildlife>).

The density of animals at the site for each of the three species was calculated based on published data available in the public domain. For harbour seal and grey seal, densities within the site were calculated by scaling the UK-wide density surfaces provided by Carter *et al.* (2020) to predict the number of seals at sea within each cell of a 5 km x 5 km grid such that the combined total number of animals added up to the total of at sea animals estimated by Carter *et al.* (2020) (150,700 for grey seal and 42,800 for harbour seal). The proposed development site is contained within a single 5 km x 5 km grid cell on the Carter seal density surfaces. The predicted number of animals for this grid cell was 7.23 (3.41 – 12.95) for harbour seal and 2.89 (0.80 – 5.52) for grey seal, giving a density for both the proposed development area of 0.29 (0.14 – 0.52) harbour seal per km² and 0.12 (0.03 – 0.22) grey seal per km².

For harbour porpoise, the most recent SCANS-III density estimate for the block containing the site of the proposed development (Block G, 0.336 harbour porpoise per km²; Hammond *et al.*, 2021) was used as the input density. Since confidence intervals around the density estimate are not provided, confidence intervals were calculated by dividing the confidence limits presented alongside the density estimate by the area of the block as calculated from the shapefile available on the SCANS website (<https://synergy.st-andrews.ac.uk/scans3/category/researchoutput>) (giving confidence limits of 0.091 – 0.555 harbour porpoise per km²). These are therefore subject to rounding error.

Since animal densities used here are already corrected for the proportion of animals not observed due to being underwater, no additional correction was required. Therefore, no correction was applied when running the ERM tool.

Proportion of animals at risk depth was then calculated using swim depth data presented within the SNH (2016) document “Assessing collision risk between underwater turbines and marine wildlife” according to the methodology presented in Box 1 of section 8.1¹.

Parameters associated with the size, shape and speed of the animals, the nature of the tidal channel and the specifications of the tidal device were then used to predict of animal encounters with the blades. Two scenarios were considered, one representing the 3.28 m diameter rotor that will be deployed initially, and the other representing the 5 m diameter rotor that will be deployed subsequently. The predictions are assumed to represent lethal collisions in the absence of avoidance. A 98% avoidance² rate was then applied to predict the final number of collisions per year. Input parameters used in the modelling are presented in Table 2.1 and Table 2.2 below.

Table 2.1: Device and site parameters used in the modelling

Parameter	Scenario 1	Scenario 2
Rotor diameter (m)	5	3.28
Rotor minimum depth (m)	3.8	4.7
Number of rotors	1	1
Number of blades	2	2
Rotor blade width (m)	0.130	0.075
Rotation speed (rpm)	34	51
Time operational (%)	36	36
Mean channel depth (m)	20.6	20.6
Mean current speed (m/s)	1.75	1.75

Table 2.1: Animal parameters used in the modelling

Parameter	Harbour porpoise	Harbour seal	Grey seal	Reference
Density (animals per km ²)	0.336 (0.091 – 0.555)	0.29 (0.14 – 0.52)	0.12 (0.03 – 0.22)	Hammond <i>et al.</i> , 2021; Carter <i>et al.</i> , 2020
Proportion at risk depth (3.28 m rotor)*	0.17	0.10	0.08	SNH, 2016; Thompson, 2015
Proportion at risk depth (5 m rotor)*	0.27	0.14	0.14	SNH, 2016
Length (m)	1.48	1.41	1.86	Thompson, 2015
Body width (m)	0.32	0.34	0.42	Thompson, 2015
Swim speed (m/s)	1.4	1.8	1.8	Westgate <i>et al.</i> , 1995; Thompson, 2015
Shape factor	0.5	0.5	0.5	SNH, 2016

* Calculated manually due to missing function in NatureScot Excel tool. For harbour seal, proportions at different depths were taken from the 0 – 20 m channel distribution rather than the 20 – 30 m channel distribution, as a precautionary approach.

¹ This was done by hand, rather than automatically using the NatureScot tool, as the function to do this within the tool was missing from the downloadable version of the tool. (NatureScot were contacted via their enquiries line on 15/11/2021 to inform them of this.)

² Recommended by NatureScot through correspondence on the 12/10/2021.

3. Results

Number of collisions predicted for harbour porpoise, harbour seal and grey seal using the ERM model are presented in Table 3.1, Table 3.2 and Table 3.3 below. Raw outputs are presented alongside predictions assuming different levels of avoidance (50%, 90%, 85%, 98% and 99%).

Table 3.1: Predicted annual collision rate for harbour porpoise at different avoidance rates (Values in bold represent the avoidance rate recommended for use by NatureScot)

Avoidance rate (%)	Scenario 1 (5 m diameter rotor)	Scenario 2 (3.28 m diameter rotor)
0 %	8.41 (2.28 – 13.89)	5.21 (1.41 – 8.61)
50 %	4.20 (1.14 – 6.94)	2.61 (0.71 – 4.31)
90 %	0.84 (0.223 – 1.39)	0.52 (0.14 – 0.86)
95 %	0.42 (0.11 – 0.69)	0.26 (0.07 – 0.43)
98 %	0.17 (0.05 – 0.28)	0.10 (0.03 – 0.17)
99	0.08 (0.02 – 0.14)	0.05 (0.01 – 0.09)

Table 3.2 Predicted annual collision rate for harbour seal at different avoidance rates (Values in bold represent the avoidance rate recommended for use by NatureScot)

Avoidance rate (%)	Scenario 1 (5 m diameter rotor)	Scenario 2 (3.28 m diameter rotor)
0 %	3.66 (1.77 – 6.57)	2.57 (1.24 – 4.60)
50 %	1.83 (0.88 – 3.28)	1.28 (0.62 – 2.30)
90 %	0.37 (0.18 – 0.66)	0.26 (0.12 – 0.46)
95 %	0.18 (0.09 – 0.33)	0.13 (0.06 – 0.23)
98 %	0.07 (0.04 – 0.13)	0.05 (0.02 – 0.09)
99	0.04 (0.02 – 0.07)	0.03 (0.01 – 0.05)

Table 3.3: Predicted annual collision rate for grey seal at different avoidance rates (Values in bold represent the avoidance rate recommended for use by NatureScot)

Avoidance rate (%)	Scenario 1 (5 m diameter rotor)	Scenario 2 (3.28 m diameter rotor)
0 %	2.00 (0.50 – 3.67)	1.16 (0.29 – 2.12)
50 %	1.00 (0.25 – 1.83)	0.58 (0.14 – 1.06)
90 %	0.20 (0.05 – 0.37)	0.12 (0.03 – 0.21)
95 %	0.10 (0.03 – 0.18)	0.06 (0.01 – 0.11)
98 %	0.04 (0.01 – 0.07)	0.02 (0.01 – 0.04)
99	0.02 (0.01 – 0.04)	0.01 (<0.01 – 0.02)

4. Discussion

The ERM modelling provides a standardised approach to generate indicative “order of magnitude” predictions of the number of collisions of marine mammals with the tidal device expected over a year (SNH, 2016). The model does not incorporate any attraction of animals towards the device, as there are no data available to quantify any such effects. However, it is important to note that the high energy flow of water through the turbine may prove attractive to marine mammals, which might result in slightly increased collision risk. In contrast, the model also assumes that all encounters result in fatality. However, some encounters will be contact with peripheral parts of the animal and/or with slow-moving central parts of the turbine and such encounters would likely result in no, or only very minor injury to the animal (SNH, 2016).

The Potential Biological Removal (PBR) value is widely used as a method of calculating whether anthropogenic mortality is consistent with the population reaching or exceeding a target population. For seal species the PBR value for West Scotland Seal Management Unit (SMU) was compared with the worst-case scenario of predicted annual collisions for both species. For harbour seal, the worst-case scenario presented here (0.07 harbour seals for the 5 m diameter rotor) constitutes just 0.007 % of the allowable take suggested by the PBR (936; SCOS, 2020). For grey seal the worst-case scenario (0.04 grey seals for the 5 m diameter rotor) constitutes just 0.004 % of the allowable take suggested by the PBR (966; SCOS, 2020).

For harbour porpoise, the site lies within the West Scotland cetacean Management Unit (MU). The population estimate for harbour porpoise within the West Scotland MU is 28,936 (21,140 – 39,608) (IAMMWG, 2021). The worst-case scenario for harbour porpoise (0.17 fatalities per year for the 5 m diameter rotor) would represent 0.0006 % of the total population within the West Scotland MU.

The percentage of the reference population estimated for harbour porpoises and percentage of PBR levels for seal species which have the potential for collision is less than 1% for the three species assessed. Therefore, collision risk is unlikely to have an adverse effect on the species populations.

5. References

Carter, M. I. D., Boehme, L., Duck, C. D., Grecian, J., Hastie, G. D., McConnell, B. J., Miller, D. L., Morris, C., Moss, S., Thompson, D., Thompson, P., and Russell, D. JF. (2020). Habitat-based predictions of at-sea distribution for grey and harbour seals in the British Isles: Report to BEIS, OESEA-16-76, OESEA-17-78. Sea Mammal Research Unit, University of St Andrews.

Hammond, P.S., Lacey, C., Gilles, A., Viquerat, S., Börjesson, P., Herr, H., Macleod, K., Ridoux, V., Santos, M.B., Scheidat, M., Teilmann, J., Vingada, J. and Øien, N. (revised 2021). Estimates of cetacean abundance in European Atlantic waters in summer 2016 from the SCANS-III aerial and shipboard surveys. Available from: https://synergy.st-andrews.ac.uk/scans3/files/2021/06/SCANS-III_design_based_estimates_final_report_revised_June_2021.pdf

IAMMWG. (2021). Updated abundance estimates for cetacean Management Units in UK waters. JNCC Report No. 680, JNCC Peterborough, ISSN 0963-8091.

SCOS. (2020). Scientific Advice on Matters Related to the Management of Seal Populations: 2020.

Scottish Natural Heritage. (2016). Assessing collision risk between underwater turbines and marine wildlife. SNH guidance note.

Thompson, D. (2015) Parameters for collision risk models. Report by Sea Mammal Research Unit, University of St. Andrews, for Scottish Natural Heritage.

Westgate, A.J., Head, A.J., Berggren, P., Koopman, H.N. & Gaskin, D.E. (1995). Diving behaviour of harbour porpoises *Phocoena phocoena*. Canadian Journal of Fisheries and Aquatic Sciences 52, 1064-73.



Creating a better environment



[naturalpower.com](https://www.naturalpower.com)
sayhello@naturalpower.com



For full details on our ISO and other certifications, please visit our website.

NATURAL POWER CONSULTANTS LIMITED, THE NATURAL POWER CONSULTANTS LIMITED, NATURAL POWER SARL, NATURAL POWER CONSULTANTS (IRELAND) LIMITED, NATURAL POWER LLC, NATURAL POWER S.A, NATURAL POWER SERVICES LIMITED AND NATURAL POWER OPERATIONS LIMITED (collectively referred to as "NATURAL POWER") accept no responsibility or liability for any use which is made of this document other than by the Client for the purpose for which it was originally commissioned and prepared. The Client shall treat all information in the document as confidential. No representation is made regarding the completeness, methodology or current status of any material referred to in this document. All facts and figures are correct at time of print. All rights reserved. VENTOS® is a registered trademark of NATURAL POWER. Melogale™, WindCentre™, ControlCentre™, ForeSite™, vuWind™, WindManager™ and OceanPod™ are trademarks of NATURAL POWER.

No part of this document or translations of it may be reproduced or transmitted in any form or by any means, electronic or mechanical including photocopying, recording or any other information storage and retrieval system, without prior permission in writing from Natural Power. All facts and figures correct at time of print. All rights reserved. © Copyright 2020.